

CONTENTS

MODEL CODE INFORMATION	CYLINDER BED SEWING MACHINE
MODEL CODE INFORMATION 2	CW SERIES 9
	LCW SERIES · · · · 9
SPECIAL SEWING MACHINE	TE / TF SERIES · · · · 9
LSWN-46BLR 3	LSC SERIES · · · · · · 10
THM-26B-1-FL 3	CK-1 10
SAM-31 3	CH SERIES · · · · · · 10
FLAT BED SEWING MACHINE	ZIG ZAG SEWING MACHINE
BBW SERIES 4	LZ2 SERIES 11
BEW SERIES 4	SKZ SERIES 11
STH-8BLD-3 4	SKZ-2B-2/3 11
WB-8GW-1 5	
LSWN SERIES 5	LONG ARM SEWING MACHINE
LSW EDGE TRIMMING SERIES 5	JW SERIES 12
LSW 2-NEEDLE SERIES 6 (SPLIT NEEDLE BAR)	BEW SERIES
SK SERIES 6	LOWINIT SERIES
TH SERIES 6	DOUBLE CHAIN STITCH SEWING MACHINE
SLH SERIES 7	, LDA SERIES 13
POST BED SEWING MACHINE	SSLD SERIES · · · · · · 13
BBWP SERIES 7	SLD SERIES · · · · · · 13
LHPWN SERIES 7	DN SERIES 14
LPW-28BLK 8	LD SERIES 14
PWB SERIES8	DCN SERIES 14
PW SERIES 8	
	AC SERVO MOTOR
	HVP-i70 15
	HVP-i90 15

^{*}Speed depends on threads, materials and type of operation.

^{*}Specification subject to change wihout notice.

MODEL CODE INFORMATION

BEW -28 BLCS-1-BTFL-CD-DS

MODEL	
C□	CYLINDER BED
P□	POST BED
J□	JUMBO BED
пппн	HIGH ARM
D D	DOUBLE CHAIN STITCH
	ZIG-ZAG STITCH
LO	AUTOMATIC LUBRICATION
ВПП	SEALED ANTI-FRICTION BEARING
□Н	VERTICAL HOOK
□W □□W	HORIZONTAL HOOK

FEED			
1	FREE FEED		
2	UPPER AND LOWER FEED		
6	LOWER FEED		
7	NEEDLE AND LOWER FEED		
8	COMPOUND FEED AND WALKING FOOT		
NE	NEEDLE		
	1-NEEDLE		
2□	2-NEEDLE		
3□	3-NEEDLE		

4□ 4-NEEDLE

SU	B-CLASS
В	REVERSE
L	LARGE HOOK
K	SPLIT NEEDLE BAR
М	TRIMMER
V	SYNCHRONIZED BINDER
R	CLOTH PULLER
GW	WHEEL FEED WITH DRIVEN ROLLER FOOT
С	THREAD TRIMMER
TA	THICK THREAD
ВТ	AUTO BACK TACK
FL	AUTO FOOT LIFT
CD	CLIMBING DEVICE
DS	DUAL STITCHING
MF	FRONT KNIFE
Н	HORIZONTAL LOWER FEED
LP	LEFT POST
20	20 INCH ARM
30	30 INCH ARM

SPECIAL SEWING MACHINE

LSWN-46BLR

4-NEEDLE FLAT BED LOCKSTITCHER

LSWN-46BLR

LOWER FEED, REVERSE, LARGE HOOK, CLOTH PULLER

- *For sewing medium weight fabrics, leather, vinyl, synthetics and laminated materials.
- *Suitable for sewing such as parachutes, tarpaulins, tents etc.

Variety	LSWN-46BLR
Max. speed	2,500s.p.m.
Max. stitch length	6.0mm
Presser foot lift	10mm(by knee) / 7mm(by hand)
Needle bar stroke	33.2mm
Needle	DP×17 #19
Thread	#30 (standard)
Hook	Large vertical axis hook(2.0times)
Lubrication	Semi-automatic type
Working space	258mm×110mm



THM-26B-1-FL

2-NEEDLE FLAT BED ORNAMENTAL STITCHING



THM-26B-1-FL

LOWER FEED, ROLLER PRESSER FOOT, REVERSE, AUTO FOOT LIFT, MOCCASSIN STITCH

- *For sewing heavy weight materials such as leather, vinyl, synthetics and rubberized fabrics etc.
- *Suitable for sewing sofas, shoe uppers, bags, jeans etc.

Variety	THM-26B-1-FL
Max. speed	550s.p.m.
Max. stitch length	8.0mm
Presser foot lift	10mm(by pedal) /9mm(by hand)
Needle bar stroke	50mm
Needle	DD×1 #24
Thread	#20 - #00(standard #2)
Needle Gauge	6.0mm
Hook	Large oscillating shuttle hook
Lubrication	Hand type
Working space	320mm×182mm



SAM-31

1-NEEDLE FLAT BED LOCKSTITCHER FOR GATHERING

SAM-31

COMPOUND FEED WAIKING FOOT, LARGE HOOK, TREAD TRIMMER, AUTO BACK TACK, AUTO FOOT LIFT

- *For sewing soft and thick materials such as leather, vinyl, synthetics and laminated and coated materials.
- *Suitable for sewing such as automobile upholstery, covers and furniture.

Variety	SAM-31
Max. speed	3,000s.p.m.
Max. stitch length	9.0mm
Presser foot lift	16mm(by auto foot lifter) / 9mm(by hand)
Needle bar stroke	34mm
Needle	DP×17 #18 - 25 (#23)
Thread	#30 - #4 (standard #8)
Hook	Large vertical axis hook(1.6times)
Amount of alternating presser foot lift	1 - 7mm
Gathering	14 kinds of gathering amount
Lubrication	Automatic lubrication type
Working space	300mm×120mm



FLAT BED SEWING MACHINE

BBW SERIES

HIGH SPEED 1-NEEDLE FLAT BED LOCKSTITCHER



BBW-8BL

COMPOUND FEED AND WALKING FOOT, REVERSE, LARGE HOOK

BBW-8BLC-BTFL-CD-DS

ABOVE FEATURES WITH THREAD TRIMMER, AUTO BACK TACK, AUTO FOOT LIFT, CLIMBING DEVICE, DUAL STITCHING DEVICE


- *For sewing medium to heavy weight materials such as leather, vinyl, synthetics and laminated and coated materials.
- *Suitable for sewing such as automobile upholstery, bags, furniture, tents tarpaulins etc.

Variety	BBW-8BLC-BTFL-CD-DS
Max. speed	3,500s.p.m.
Max. stitch length	9.0mm
Presser foot lift	16mm(by auto foot lift) / 9mm(by hand)
Needle bar stroke	34mm
Needle	DP×17 #18 - 25 (#23), 135×17 #120 - #200 (#160)
Thread	#30 - #4 (standard #8)
Hook	Large vertical axis hook(1.6times)
Amount of alternating presser foot lift	1 - 7mm
Lubrication	Automatic lubrication type
Working space	300mm×120mm



BEW SERIES

HIGH SPEED FLAT BED LOCKSTITCHER



BEW-8BLS-1

1-NEEDLE, COMPOUND FEED AND WALKING FOOT, REVERSE, LARGE HOOK, S TYPE PRESSER FOOT

BEW-8BLCS-1-BTFL-CD-DS

1-NEEDLE, ABOVE FEATURES WITH THREAD AUTO BACK TACK, AUTO FOOT LIFT, CLIMBING DEVICE, DUAL STITCHING DEVICE, S TYPE PRESSER FOOT

BEW-28BLS-1

2-NEEDLE, COMPOUND FEED AND WALKING FOOT, REVERSE, LARGE HOOK, S TYPE PRESSER FOOT

BEW-28BLCS-1-BTFL-CD-DS

2-NEEDLE, ABOVE FEATURES WITH THREAD TRIMMER, AUTO BACK TACK, AUTO FOOT LIFT, CLIMBING DEVICE, DUAL STITCHING DEVICE, S TYPE PRESSER FOOT

*E type presser foot is available as an option.

- *For sewing medium to heavy weight materials such as leather, vinyl, synthetics and laminated and coated materials.
- *Suitable for sewing such as automobile upholstery, bags, furniture, tents, tarpaulins etc.

Variety	BEW-8BLCS-1-BTFL-CD-DS
Max. speed	2,500s.p.m.
Max. stitch length	9.0mm
Presser foot lift	16mm(by auto foot lift) / 9mm(by hand)
Needle bar stroke	37mm
Needle	DP×17 #18 - #25 (#23), 135×17 #110 - #200 (#160)
Thread	#30 - #1 (standard #5)
Hook	Large vertical axis hook(2.0times)
Amount of alternating presser foot lift	1 - 7mm
Lubrication	Automatic lubrication type
Working space	300mm×120mm



STH-8BLD-3

1-NEEDLE FLAT BED LOCKSTITCHER

STH-8BLD-3

COMPOUND FEED AND WALKING FOOT, REVERSE, LARGE HOOK

- *For sewing medium to heavy weight materials such as leather, vinyl, plastics, synthetics and laminated and coated materials.
- *Suitable for sewing automobile upholstery, furniture, tarpaulins, awnings, tents, umbrellas, handbags, luggage, inflatable, outdoor clothing, foundation garments, sports and camping equipments etc.

Variety	STH-8BLD-3
Max. speed	2,000s.p.m./2,400s.p.m.(8mm or less)
Max. stitch length	10mm
Presser foot lift	13mm(by knee) /8.5mm(by hand)
Needle bar stroke	33.2mm
Needle	DP×17 #22, 135×17 #140
Thread	#8 (standard)
Hook	Large horizontal axis hook(2.0times)
Amount of alternating presser foot lift	2.7 - 5.5mm (Standard 3.2mm)
Lubrication	Hand type
Working space	258mm×110mm



WB-8GW-1

HIGH SPEED 1-NEEDLE FLAT BED LOCKSTITCHER

WB-8GW-1

WHEEL FEED AND DRIVEN ROLLER PRESSER

- *For sewing medium to heavy weight materials such as leather, vinyl, plastics, synthetics laminated and coated materials.
- *Suitable for sewing shoe uppers, bags, hollow, tubular and curved articles etc.

Variety	WB-8GW-1
Max. speed	3,000s.p.m.
Max. stitch length	5.0mm
Presser foot lift	9mm (by knee) / 7mm (by hand)
Needle bar stroke	38mm
Needle	DP×7 #16 (standard)
Thread	#20 (standard)
Hook	Vertical axis hook
Lubrication	Semi-automatic type
Working space	260mm×110mm



LSWN SERIES

HIGH SPEED FLAT BED LOCKSTITCHER

LSWN-8BL-3

1-NEEDLE, COMPOUND FEED AND WALKING FOOT, REVERSE, LARGE HOOK

LSWN-8BLV-3

1-NEEDLE, COMPOUND FEED AND WALKING FOOT, REVERSE, LARGE HOOK, SYNCHRONIZED BINDER

LSWN-28BL-3

2-NEEDLE, COMPOUND FEED AND WALKING FOOT, REVERSE, LARGE HOOK

*For sewing medium to heavy weight materials such as leather, vinyl, plastics, synthetics and laminated and coated materials.

*Suitable for sewing automobile upholstery, furniture, tarpaulins, awnings, tents, umbrellas, handbags, luggage, inflatable, outdoor clothing, foundation garments, sports and camping equipments etc.

Variety	LSWN-8BL-3
Max. speed	2,800s.p.m.
Max. stitch length	10mm
Presser foot lift	16mm(by knee) /8.5mm(by hand)
Needle bar stroke	33.2mm
Needle	DP×17 #22, 135×17 #140
Thread	#8 (standard)
Hook	Large vertical axis hook(2.0times)
Amount of alternating presser foot lift	3 - 6mm (Standard 4mm)
Lubrication	Semi-automatic type
Working space	258mm×110mm



LSW EDGE TRIMMING SERIES

HIGH SPEED 1-NEEDLE FLAT BED LOCKSTITCHER

LSW-8LVMF

COMPOUND FEED AND WALKING FOOT, LARGE HOOK, SYNCHRONIZED BINDER, VERTICAL EDGE TRIMMING (FRONT)

LSW-8BLVMF

COMPOUND FEED AND WALKING FOOT, REVERSE, LARGE HOOK, SYNCHRONIZED BINDER, VERTICAL EDGE TRIMMING (FRONT)

LSW-8BLM

COMPOUND FEED AND WALKING FOOT, REVERSE, LARGE HOOK, VERTICAL EDGE TRIMMING (RIGHT)

*Available various customized binder at extra cost.

- *For sewing medium to heavy weight materials such as leather, vinyl, plastics, synthetics laminated and coated materials.
- *Designed for operation such as tape binding, edge trimming for quilt, cushion, cover and interior etc.

Variety	LSW-8BLVMF
Max. speed	2,500s.p.m.
Max. stitch length	6.2mm
Presser foot lift	12mm(by knee) /8.5mm(by hand)
Needle bar stroke	33.2mm
Needle	MT×190 #19, 190R #120
Thread	#30 (standard)
Hook	Large vertical axis hook(2.0times)
Amount of alternating presser foot lift	3 - 6mm (Standard 4mm)
Lubrication	Semi-automatic type





LSW 2-NEEDLE SERIES (SPLIT NEEDLE BAR)

HIGH SPEED 2-NEEDLE FLAT BED LOCKSTITCHER













LSW-28BLK

COMPOUND FEED AND WALKING FOOT, REVERSE, LARGE HOOK, SPLIT NEEDLE BAR *For sewing medium to heavy weight materials such as leather, coats, jackets and jeans which require decorative or functional angular stitching.

Variety	LSW-28BLK
Max. speed	2,400s.p.m.
Max. stitch length	6.5mm
Presser foot lift	13mm(by knee) /8.5mm(by hand)
Needle bar stroke	32.6mm
Needle	DP×17 #22, 135×17 #140
Thread	#8 (standard)
Hook	Large vertical axis hook(2.0times)
Amount of alternating presser foot lift	3 - 6mm (Standard 4mm)
Lubrication	Semi-automatic type
Working space	258mm×110mm



SK SERIES

EXTRA HEAVY DUTY FLAT BED LOCKSTITCHER













SK-2B-1

1-NEEDLE, UPPER AND LOWER FEED, REVERSE, LARGE HOOK

SK-2B-1-20

1-NEEDLE, UPPER AND LOWER FEED, REVERSE, LARGE HOOK, 20 INCH LONG ARM

- *For sewing heavy weight materials such as leather, canvas, vinyl, plastics, laminated and coated materials.
- *Suitable for sewing such products as harnesses, covers, safety belts, tents, sheets, gloves, buffing wheels etc.

	Variety	SK-2B-1
Max. speed		1,200s.p.m.
	Max. stitch length	13mm
	Presser foot lift	14mm(by knee) /13mm(by hand)
	Needle bar stroke	50.8mm
	Needle	DD×1 #24, 328 #180
	Thread	#0 - #5 (standard #5)
	Hook	Large horizontal axis hook
	Amount of alternating presser foot lift	3 - 6mm (Standard 4mm)
	Lubrication	Hand type
	Working space	253mm×190mm



TH SERIES

EXTRA HEAVY DUTY FLAT BED LOCKSTITCHER









TH-8B

1-NEEDLE, COMPOUND FEED AND WALKING FOOT, REVERSE, OSCILLATING SHUTTLE HOOK

- *For sewing heavy weight materials such as canvas, leather, vinyl, plastics, synthetics and laminated and coated materials.
- *Suitable for sewing tents, sails, harnesses, safety belts, parachutes, balloons, industrial bags, book bindings, suitcases and other extra heavy weight materials.

Variety	TH-8B
Max. speed	800s.p.m.
Max. stitch length	12mm
Presser foot lift	25mm(by pedal) / 10mm(by hand)
Needle bar stroke	56mm
Needle	DY×3 #25, 794 #200
Thread	#8 - #0 (standard #5)
Hook	Large oscillating shuttle hook
Amount of alternating presser foot lift	3 - 6mm (Standard 4mm)
Lubrication	Hand type
Working space	400mm×180mm



SLH SERIES

1-NEEDLE EXTRA HEAVY DUTY FLAT BED LOCKSTITCHER



SLH-2B

UPPER AND LOWER FEED, REVERSE

SLH-2B-FH-1

UPPER AND LOWER FEED, REVERSE, 32MM FOOT LIFT

SLH-2B-FH-1H

UPPER AND LOWER FEED, REVERSE, 40MM FOOT LIFT

- *For sewing extra heavy weight materials.
- *Suitable for sewing such as safety and logging belts, cargo slings, buffing wheels, harnesses, parachutes, saddlery, balloon etc.

Variety	SLH-2B-FH-1
Max. speed	700s.p.m.
Max. stitch length	15mm
Presser foot lift	32mm(by pedal) /29mm(by hand)
Needle bar stroke	66mm
Needle	Schmetz 1000 (#250)
Thread	#0 (standard) - #00
Hook	Large oscillating shuttle hook
Amount of alternating presser foot lift	5 - 7mm (standard 6mm)
Lubrication	Hand type
Working space	413mm×218mm



POST BED SEWING MACHINE

BBWP SERIES

POST BED LOCKSTITCHER













BBWP-8BL

1-NEEDLE, COMPOUND FEED AND WALKING FOOT, REVERSE, LARGE HOOK

BBWP-8BL-BTFL

ABOVE FEATURES WITH AUTO BACK TACK, AUTO FOOT LIFT

BBWP-8BLC-BTFL-CD-DS

ABOVE FEATURES WITH THREAD TRIMMER, CLIMBING DEVICE, DUAL STITCHING DEVICE

BBWP-28BL

2-NEEDLE, COMPOUND FEED AND WALKING FOOT, REVERSE, LARGE HOOK

BBWP-28BL-BTFL

ABOVE FEATURES WITH AUTO BACK TACK, AUTO FOOT LIFT

BBWP-28BLC-BTFL-CD-DS

ABOVE FEATURES WITH THREAD TRIMMER, CLIMBING DEVICE, DUAL STITCHING DEVICE

- *For sewing medium to heavy weight materials such as leather, vinyl, synthetics and laminated and coated materials.
- *Suitable for sewing such as automobile upholstery, tarpaulins, covers, awnings, bags, tents, shoes etc.

Variety	BBWP-8BL(28BL)
Max. speed	2,500s.p.m.
Max. stitch length	9.0mm
Presser foot lift	9mm(by knee) /16mm(by hand)
Needle bar stroke	34mm
Needle	DP×17 #24
Thread	#5
Hook	Large vertical axis hook(2.0times)
Amount of alternating presser foot lift	1 - 7mm
Lubrication	Semi-automatic type
Post height	178mm



LHPWN SERIES

1-NEEDLE HIGH POST BED LOCKSTITCHER

LHPWN-8BL-3-LP

COMPOUND FEED AND WALKING FOOT, REVERSE, LARGE HOOK, LEFT POST

LHPWN-8B-3-SF-LP

COMPOUND FEED AND WALKING FOOT, REVERSE, STANDARD HOOK, SLIM POST, LEFT POST

- *For sewing medium to heavy weight materials such as leather, vinyl, synthetics and laminated and coated materials.
- *Suitable for sewing such as automobile upholstery, tarpaulins, covers, awnings, bags, tents, shoes etc.

Variety	LHPWN-8B-3-SF-LP
Max. speed	1,600s.p.m.
Max. stitch length	5.0mm
Presser foot lift	16mm(by pedal) / 10mm(by hand)
Needle bar stroke	35.4mm
Needle	DP×17 #22, 135×17 #140
Thread	#8
Hook	Vertical axis hook
Amount of alternating presser foot lift	2.7 - 5.5mm
Lubrication	Semi-automatic type
Post height	445mm



LPW-28BLK



2-NEEDLE POST BED LOCKSTITCHER (SPLIT NEEDLE BAR)

LPW-28BLK COMPOUND FEED AND WALKING FOOT, REVERSE, LARGE HOOK, SPLIT NEEDLE BAR

- *For sewing medium to heavy weight materials such as leather, vinyl, synthetics and laminated and coated materials.
- *Suitable for sewing such as automobile upholstery, bags, shoe upper, jackets, ornamental stitching etc.

Variety	LPW-28BLK
Max. speed	2,200s.p.m.
Max. stitch length	5.5mm
Presser foot lift	14mm(by knee) /8.5mm(by hand)
Needle bar stroke	32.6mm
Needle	DP×17 #24, 135×17 #180
Thread	#5 (standard)
Hook	Large vertical axis hook
Amount of alternating presser foot lift	2.5 - 5mm (standard 3.2mm)
Lubrication	Semi-automatic type
Post height	178mm



PWB SERIES

HIGH SPEED POST BED WHEEL AND DRIVEN FEED LOCKSTITCHER



PWB-8GW-1

1-NEEDLE

PWB-8GWC-1

1-NEEDLE, THREAD TRIMMER

PWB-8GWC-1-QNU

1-NEEDLE, THREAD TRIMMER, QUICK NEEDLE UP

PWB-22GW-1

2-NEEDLE

PWB-22GWC-1

2-NEEDLE, THREAD TRIMMER

PWB-22GWC-1-QNU

2-NEEDLE, THREAD TRIMMER, QUICK NEEDLE UP

*For sewing leather,	vibral mlastics				
"For sewing learner	VIDVI DIASTICS	synthetics	ano iaminateo	and (coated materials

*Suitable for sewing such as shoe upper, hollow, tubular and curved articles etc.

Variety	PWB-8GW-1	PWB-22GW-1
Max. speed	3,000s.p.m.	2,500s.p.m.
Max. stitch length	5.0mm	4.0mm
Presser foot lift	7mm(by knee)	/7mm(by hand)
Needle bar stroke	38	mm
Needle	DP×7 #14	, 134R #90
Thread	#30 (st	andard)
Hook	Vertical	axis hook
Lubrication	Simplified Sem	i-automatic type
Post height	178	3mm



PW SERIES

HIGH SPEED POST BED LOWER FEED LOCKSTITCHER

PW-6B-1

1-NEEDLE, REVERSE

PW-26B-1

2-NEEDLE, REVERSE

- *For sewing medium to heavy weight materials such as leather, vinyl, plastics, synthetics and laminated and coated materials.
- *Suitable for sewing such as shoe upper, raincoats, underwear, overalls, foundation garments etc.

Variety	PW-6B-1	PW-26B-1
Max. speed	2,800	s.p.m.
Max. stitch length	4	5mm
Presser foot lift	8mm(by knee)	/6mm(by hand)
Needle bar stroke	33.2mm	
Needle	DP×F22 #14, 134×KKS #90	
Thread	#30 (standard)	
Hook	Vertical axis hook	
Lubrication	Hand type	
Post height	178	Bmm



CYLINDER BED SEWING MACHINE

CW SERIES

1-NEEDLE CYLINDER BED LOCKSTITCHER









CW-1

FREE FEED

CW-7B

NEEDLE AND LOWER FEED, REVERSE

CW-8B-2

COMPOUND FEED AND WALKING FOOT, REVERSE

- *For darning and mending all types of medium to heavy weight materials. (CW-1)
- *Designed for stitching tubular and curved work.
- *Suitable for sewing such products as caps, cushions, boots, shoes, bags, luggage, handbags etc. (except CW-1)

Variety	CW-8B-2
Max. speed	2,500s.p.m.
Max. stitch length	5mm
Presser foot lift	14mm(by pedal) /8.5mm(by hand)
Needle bar stroke	33.2mm
Needle	DP×17 #22, 135×17 #140
Thread	#8 (standard)
Hook	Vertical axis hook
Amount of alternating presser foot lift	2.7 - 5.5mm (standard 3.2mm)
Lubrication	Hand type
Cylinder size	65mm



LCW SERIES

CYLINDER BED LARGE HOOK LOCKSTITCHER











M

LCW-8BL

1-NEEDLE, COMPOUND FEED AND WALKING FOOT, REVERSE

LCW-8BL-1

1-NEEDLE, COMPOUND FEED AND WALKING FOOT, REVERSE, SMALL SIZED CYLINDER EDGE

LCW-8BLV

1-NEEDLE, COMPOUND FEED AND WALKING FOOT, REVERSE, SYNCHRONIZED BINDER

LCW-8BLV-1

1-NEEDLE, COMPOUND FEED AND WALKING FOOT, REVERSE, SYNCHRONIZED BINDER, SMALL SIZED CYLINDER EDGE

LCW-28BL

2-NEEDLE, COMPOUND FEED AND WALKING FOOT,

LCW-28BL-20 2-NEEDLE, COMPOUND FEED AND WALKING FOOT, REVERSE, 20 INCH LONG ARM

LCW-28BL-30

2-NEEDLE, COMPOUND FEED AND WALKING FOOT, REVERSE, 30 INCH LONG ARM

*For sewing medium to heavy weight materials such as leather, vinyl, plastics, s	synthetics
and laminated and coated materials	

*Suitable for sewing tubular and curved work such as bags, handbags, shoes, boots, saddlery etc.

Variety	LCW-8BL
Max. speed	2,000s.p.m.
Max. stitch length	6.2mm
Presser foot lift	14mm(by pedal) /8.5mm(by hand)
Needle bar stroke	33.2mm
Needle	DP×17 #22, 135×17 #140
Thread	#8 (standard)
Hook	Large vertical axis hook
Amount of alternating presser foot lift	2.7 - 5.5mm (standard 3.2mm)
Lubrication	Semi-automatic type
Cylinder size	77mm



(RIGHT SIDE PULLEY) TF SERIES (LEFT SIDE PULLEY)

1-NEEDLE CYLINDER BED OSCILLATING SHUTTLE HOOK LOCKSTITCHER



TE-6B

LOWER FEED, REVERSE

TF-6

LOWER FEED

TF-6B

LOWER FEED, REVERSE

- *For sewing light to medium heavy weight materials such as leather, vinyl, synthetics and laminated and coated materials.
- *Suitable for sewing such as shoe upper, bags, gloves, hollow, tubular and curved articles etc.

Variety	TE-6B
Max. speed	1,400s.p.m.
Max. stitch length	4.5mm
Presser foot lift	10mm(by knee) / 7mm(by hand)
Needle bar stroke	36mm
Needle	DB×1 #19, 16×231 #120
Thread	#20 (standard)
Hook	Long beak oscillating shuttle hook
Lubrication	Hand type
Cylinder size	61.5mm



LSC SERIES

1-NEEDLE NARROW CYLINDER BED LOCKSTITCHER



LSC-8B-2

COMPOUND FEED AND WALKING FOOT, REVERSE, STANDARD HOOK

LSC-8BV-2

COMPOUND FEED AND WALKING FOOT, REVERSE, STANDARD HOOK, SYNCHRONIZED BINDER

LSC-8BLH-1

COMPOUND FEED AND WALKING FOOT, REVERSE, LARGE HOOK, HORIZONTAL LOWER FEED

LSC-8BLV-1

COMPOUND FEED AND WALKING FOOT, REVERSE, LARGE HOOK, SYNCHRONIZED BINDER

LSC-8BHC

COMPOUND FEED AND WALKING FOOT, REVERSE, STANDARD HOOK, HORIZONTAL FEED, THREAD TRIMMER *For sewing medium to heavy weight materials such as leather, vinyl, plastics, synthetics and laminated and coated materials.

*Suitable for sewing tubular and curved work such as bags, handbags, shoes, boots, hats etc.

Variety	LSC-8B-2
Max. speed	2,300s.p.m.
Max. stitch length	6.0mm
Presser foot lift	13mm(by pedal) /8.5mm(by hand)
Needle bar stroke	33.2mm
Needle	DP×17 #18, 135×17 #110
Thread	#20 (standard)
Hook	Horizontal axis hook
Amount of alternating presser foot lift	3 - 6mm (standard 4mm)
Lubrication	Semi-automatic type
Cylinder size	46mm



CK-1

EXTRA HEAVY DUTY CYLINDER BED LOCKSTITCHER



CK-1

1-NEEDLE, FREE FEED

*For darning of tents, sheets, and tubular products, especially suitable for darning jute sacks.

Variety	CK-1
Max. speed	1,200s.p.m.
Needle bar stroke	50.8mm
Needle	DD×1 #24, 328 #180
Thread	#8 - #0
Hook	Extra large horizontal axis hook
Lubrication	Semi-automatic type
Cylinder size	101mm × 108mm



CH SERIES

EXTRA HEAVY DUTY CYLINDER BED LOCKSTITCHER



CH-7B

1-NEEDLE, NEEDLE AND LOWER FEED, REVERSE, and coated materials.

LARGE OSCILLATING SHUTTLE HOOK *Suitable for sewing tu

CH-8B

1-NEEDLE,

COMPOUND FEED AND WALKING FOOT,
REVERSE, LARGE OSCILLATING SHUTTLE HOOK

- *For sewing heavy weight materials such as canvas, leather, vinyl, plastics, synthetics and laminated and coated materials.
- *Suitable for sewing tubular and curved work such as bags, shoes, boots, saddlery etc.

CH-8B
800s.p.m.
10mm
25mm(by pedal) /10mm(by hand)
56mm
DY×3 #24, 794 #180
#8 - #0 (standard #5)
Large oscillating shuttle hook
3 - 6mm (standard 4mm)
Hand type
82mm



ZIG ZAG SEWING MACHINE

LZ2 SERIES

\leq



1-NEEDLE FLAT BED ZIG ZAG FOR LIGHT TO MEDIUM DUTY

LZ2-990-2N

LOWER FEED, REVERSE, LARGE HOOK, 2-POINT (1-STEP) ZIGZAG

LZ2-992-2N

UPPER AND LOWER FEED, REVERSE, LARGE HOOK, 2-POINT (1-STEP) ZIGZAG

LZ2-990-3N

LOWER FEED. REVERSE. LARGE HOOK

LZ2-992-3N

UPPER AND LOWER FEED REVERSE, LARGE HOOK, 3-POINT (2-STEP) ZIGZAG 3-POINT (2-STEP) ZIGZAG

LZ2-990-4N

LARGE HOOK

LZ2-992-4N

LOWER FEED, REVERSE, UPPER AND LOWER FEED, REVERSE, LARGE HOOK, 4-POINT (3-STEP) ZIGZAG 4-POINT (3-STEP) ZIGZAG

*Long arm type (20 inch and 30 inch) and 2-needle machine are also available as an option.

- *For sewing light to medium weight materials such as leather, vinyl, canvas materials.
- *Suitable for sewing such as shoe upper, leather gloves, leather garment, wet suit, nets etc.

	Variety	LZ2-990-2N
),	Max. speed	2,800s.p.m.
	Max. stitch length	5.0mm
	Presser foot lift	9mm(by knee) / 8mm(by hand)
	Needle bar stroke	34.6mm
,	Zig-Zag width	0 - 10mm
	Needle	DP×17 #19
	Thread	#30 (standard)
	Hook	Large horizontal axis hook
	Lubrication	Semi-automatic type
	Working space	258mm×110mm



SKZ SERIES

1-NEEDLE FLAT BED EXTRA LARGE HOOK ZIG ZAG FOR HEAVY DUTY

	**	ļ	· · · · · · · · · · · · · · · · · · ·	∯ ⊚⊙ ⊙	ঘ	M	H	XH
--	-----------	---	---------------------------------------	------------------	---	---	---	----

SKZ-6 LOWR FEED

2-POINT (1-STEP) SKZ-6-3

LOWR FEED, 3-POINT (2-STEP)

SKZ-6-4 LOWR FEED. 4-POINT (3-STEP)

SKZ-6B

LOWR FEED, REVERSE, 2-POINT (1-STEP)

SKZ-6B-3

LOWR FEED, REVERSE, 3-POINT (2-STEP)

SKZ-6B-4

LOWR FEED. REVERSE. 4-POINT (3-STEP)

*Cloth puller (R) is available as an option

*26 inch long arm is available as an option

*For sewing medium	to heavy weight	t materials such as	s leather,	canvas and	vinyl.

*Suitable for sewing such as automobile upholstery, furniture, luggage, rope, blankets, nets, carpets,

Variety	SKZ-6-4
Max. speed	1,000s.p.m.
Max. stitch length	7.5mm
Presser foot lift	11mm(by knee) / 10mm(by hand)
Needle bar stroke	50.8mm
Zig-Zag width	0 - 12.7mm
Needle	DP×H14 #25
Thread	#5 (standard)
Hook	Extra large horizontal axis hook
Lubrication	Hand type
Working space	254mm×195mm



SKZ-2B-2/3

1-NEEDLE FLAT BED EXTRA LARGE HOOK ZIG ZAG FOR HEAVY DUTY



SKZ-2B-2/3

UPPER AND LOWR FEED REVERSE 2-POINT (1-STEP) AND 3-POINT (2-STEP) CHANGE OVER

*For sewing medium to heavy weight materials such as leather, canvas and vinyl.

≶


*Suitable for sewing such as automobile upholstery, furniture, luggage, rope, blankets, nets, carpets, sail etc.

Variety	SKZ-2B-2/3
Max. speed	1,000s.p.m.
Max. stitch length	7.5mm
Presser foot lift	15mm(by knee) / 9mm(by hand)
Needle bar stroke	50.8mm
Zig-Zag width	0 - 12.7mm
Needle	DP×H14 #25
Thread	#5 (standard)
Hook	Extra large horizontal axis hook
Amount of alternating presser foot lift	3 - 6mm
Lubrication	Hand type
Working space	254mm×195mm



LONG ARM SEWING MACHINE

JW SERIES





JW-8BL-30-3

1-NEEDLE, COMPOUND FEED AND WALKING FOOT, REVERSE, EXTRA LARGE HOOK

JW-28BL-30-3

2-NEEDLE, COMPOUND FEED AND WALKING FOOT, REVERSE, EXTRA LARGE HOOK

JW-8BLC-30-3

1-NEEDLE, COMPOUND FEED AND WALKING FOOT, REVERSE, EXTRA LARGE HOOK, THREAD TRIMMER

JW-28BLC-30-3

2-NEEDLE, COMPOUND FEED AND WALKING FOOT, REVERSE, EXTRA LARGE HOOK, THREAD TRIMMER

*Cloth puller (R), auto back tack (BT) and auto foot lift (FL) are available as an option

- *For sewing extra heavy weight materials such as canvas, vinyl, leather, synthetics, various coated, laminated and rubberized materials.
- *Suitable for sewing such as tents, tarps, awnings, truck covers, auto marine and furniture upholstery, field covers, fabrics structures and heavy bulky products.

Variety	JW-28BL-30-3
Max. speed	1,200s.p.m.
Max. stitch length	10mm
Presser foot lift	23mm(by pedal)/20mm(by hand)
Needle bar stroke	46.8mm
Needle	DY×3 #24
Thread	#5 (standard)
Hook	Special extra large vertical axis hook
Amount of alternating presser foot lift	6 - 9mm (standard 6mm)
Lubrication	Semi-automatic type
Working space	762mm×153mm



BEW SERIES

FLAT BED LONG ARM (30 INCH) LOCKSTITCHER

BEW-8BLS-30

1-NEEDLE, COMPOUND FEED AND WALKING FOOT, REVERSE, LARGE HOOK

BEW-8BLCS-30-BTFL-CD-DS

1-NEEDLE, COMPOUND FEED AND WALKING FOOT, REVERSE, LARGE HOOK, THREAD TRIMMER, AUTO BACK TACK, AUTO FOOT LIFT, CLIMBING DEVICE, DUAL STITCHING

BEW-28BLS-30

2-NEEDLE, COMPOUND FEED AND WALKING FOOT, REVERSE, LARGE HOOK

BEW-28BLCS-30-BTFL-CD-DS

2-NEEDLE, COMPOUND FEED AND WALKING FOOT, REVERSE, LARGE HOOK, THREAD TRIMMER, AUTO BACK TACK, AUTO FOOT LIFT, CLIMBING DEVICE, DUAL STITCHING

*For sewing medium to heavy weight materials such as leather, canvas, vinyl, synthetics and laminated and coated materials.

*Suitable for sewing such as automobile upholstery, tarpaulins, covers, awnings, tents, luggage, sports and camping equipment etc.

Variety	BEW-8BLCS-30- BTFL-CD-DS
Max. speed	2,000s.p.m.
Max. stitch length	9.0mm
Presser foot lift	9mm(by hand) / 16mm(by auto foot lift)
Needle bar stroke	37mm
Needle	DP×17 #23, 135×17 #160
Thread	#30 - #1 (standard #5)
Hook	Large vertical axis hook(2.0times)
Amount of alternating presser foot lift	1 - 7mm
Lubrication	Semi-automatic type
Working space	770mm×120mm



M

LSWNH SERIES

FLAT BED LONG ARM (20 INCH) HIG ARM (6 INCH) LOCKSTITCHER

LSWNH-8BL-20

1-NEEDLE, COMPOUND FEED AND WALKING FOOT, REVERSE, LARGE HOOK

LSWNH-28BL-20

2-NEEDLE, COMPOUND FEED AND WALKING FOOT, REVERSE, LARGE HOOK

*Auto back tack (BT) and auto foot lift (FL) are available as an option

- *For sewing medium to heavy weight materials such as leather, canvas, vinyl, synthetics and laminated and coated materials.
- *Suitable for sewing such as automobile upholstery, tarpaulins, covers, awnings, tents, luggage, sports and camping equipment etc.

Variety	LSWNH-28BL-20
Max. speed	2,000s.p.m.
Max. stitch length	10mm
Presser foot lift	16mm(by knee)/8.5mm(by hand)
Needle bar stroke	35.4mm
Needle	DP×17 #22, 135×17 #140
Thread	#8 (standard)
Hook	Large vertical axis hook(2.0times)
Amount of alternating presser foot lift	3 - 6mm (standard 4mm)
Lubrication	Semi-automatic type
Working space	516mm×150mm



DOUBLE CHAIN STITCH SEWING MACHINE

LDA SERIES

HIGH SPEED FEED OFF THE ARM DOUBLE CHAIN STITCH



LDA-L26-1

2-NEEDLE, LOWER FEED FOR LIGHT WEIGHT MATERIALS

LDA-T26-1

2-NEEDLE, LOWER FEED FOR **HEAVY WEIGHT MATERIALS**

- *For sewing light to heavy weight materials.
- *Suitable for sewing such as T-shirts, shirt, sleep suit, uniforms, skirts, pants, jeans, heavy overalls, raincoats, difficult to sew tubular products etc.

Variety	LDA-L26-1	LDA-T26-1
Max. speed	6,500s.p.m.	5,000s.p.m.
Max. stitch length	2.5mm	4.2mm
Presser foot lift	6.4mm	8.0mm
Needle bar stroke	27mm	33.3mm
Needle	TV×7 #16	TV×3 #21
Needle	149×7 #100	149×3 #130
Thread #40 (standard)		#20 (standard)
Lubrication	Full Automatic type	



SSLD SERIES

HEAVY DUTY ULTRA LONG ARM MULTI-NEEDLE DOUBLE CHAIN STITCH

SSLD-□8R (2 TO 9 NEEDLES) COMPOUND FEED AND WALKING FOOT,

CLUTCH DRIVEN PULLER FEED

SSLD-1 8R (10 TO 18 NEEDLES) COMPOUND FEED AND WALKING FOOT,

CLUTCH DRIVEN PULLER FEED

*For sewing medium to heavy weight	t fabrics, leather	, canvas, denim,	synthetics, a	and various o	coated
and laminated materials.					

*Suitable for sewing automobile upholstery, sofas, carpets, mattresses, etc.

)	Variety	SSLD-28R
	Max. speed	1,200s.p.m.
	Max. stitch length	9.0mm
	Presser foot lift	15mm
	Needle bar stroke	39mm
	Needle	DV×59 #24, 62×59 #140
	Thread	#8 (standard)
	Amount of alternating presser foot lift	2 - 5.8mm (standard 3.6mm)
	Lubrication	Hand type
	Working space	508mm×122mm



M

Н

SLD SERIES

HEAVY DUTY LONG ARM DOUBLE CHAIN STITCH

SLD-28R-1

2-NEEDLE, COMPOUND FEED AND WALKING FOOT, CLUTCH DRIVEN PULLER FEED, WITH PNEUMATIC PRESSURE CONTROL

SLD-38R-1

3-NEEDLE, COMPOUND FEED AND WALKING FOOT, CLUTCH DRIVEN PULLER FEED, WITH PNEUMATIC PRESSURE CONTROL

SLD-48R-1

4-NEEDLE, COMPOUND FEED AND WALKING FOOT, CLUTCH DRIVEN PULLER FEED, WITH PNEUMATIC PRESSURE CONTROL

- *For sewing medium to heavy weight fabrics, leather, canvas, denim, synthetics, and various coated and laminated materials.
- *Suitable for sewing automobile upholstery, sofas, carpets, mattresses, etc.

Variety	SLD-28R-1
Max. speed	2,500s.p.m.
Max. stitch length	7.6mm
Presser foot lift	11mm
Needle bar stroke	36.5mm
Needle	DV×59 #22, 62×59 #140
Thread	#8 (standard)
Amount of alternating presser foot lift	1 - 5mm (standard 2.5mm)
Lubrication	Hand type
Working space	525mm×135mm



DN SERIES

HIGH SPEED FLAT BED DOUBLE CHAIN STITCH



DN-8-AP

1-NEEDLE, COMPOUND FEED AND WALKING FOOT, PNEUMATIC PRESSURE CONTROL

DN-8R-AP

1-NEEDLE, COMPOUND FEED AND WALKING FOOT, PNEUMATIC PRESSURE CONTROL, CLOTH PULLER

DN-28-AP

2-NEEDLE, COMPOUND FEED AND WALKING FOOT, PNEUMATIC PRESSURE CONTROL

DN-28R-AP

2-NEEDLE, COMPOUND FEED AND WALKING FOOT, PNEUMATIC PRESSURE CONTROL, CLOTH PULLER

- *For sewing medium to heavy weight fabrics, leather, canvas, denim, synthetics, and various coated and laminated materials.
- *Suitable for sewing automobile upholstery, sofas, carpets, mattresses, etc.

Variety	DN-8-AP
Max. speed	3,500s.p.m.
Max. stitch length	7.6mm
Presser foot lift	11mm
Needle bar stroke	36.5mm
Needle	DV×59 #22, 62×59 #140
Thread	#8 (standard)
Amount of alternating presser foot lift	1 - 5mm (standard 2.5mm)
Lubrication	Hand type
Working space	270mm×135mm



LD SERIES

HIGH SPEED AUTOMATIC LUBRICATION FLAT BED DOUBLE CHAIN STITCH



LD-7

1-NEEDLE, NEEDLE AND LOWER FEED

LD-27

2-NEEDLE, NEEDLE AND LOWER FEED

LD-8

1-NEEDLE, COMPOUND FEED AND WALKING FOOT

LD-28

2-NEEDLE, COMPOUND FEED AND WALKING FOOT

- *Cloth puller (R) is available at an extra cost.
- *3 to 6 needle machine is available in special order.

- *For sewing medium to heavy weight fabrics, leather, canvas, denim, synthetics, and various coated and laminated materials.
- *Suitable for sewing automobile upholstery, sofas, carpets, mattresses, etc.

Variety	LD-27R
Max. speed	3,000s.p.m.
Max. stitch length	7.5mm
Presser foot lift	13mm(by knee) / 8mm(by hand)
Needle bar stroke	35mm
Needle	DV×59 #22, 62×59 #140
Thread	#8 (standard)
Lubrication	Full Automatic type
Working space	270mm×135mm



DCN SERIES

HIGH SPEED CYLINDER BED DOUBLE CHAIN STITCH



DCN-7

1-NEEDLE, NEEDLE AND LOWER FEED

DCN-27

2-NEEDLE, NEEDLE AND LOWER FEED

DCN-47

4-NEEDLE, NEEDLE AND LOWER FEED

DCN-25R

2-NEEDLE, NEEDLE AND GEAR DRIVEN PULLER FEED

DCN-45R

4-NEEDLE, NEEDLE AND GEAR DRIVEN PULLER FEED

*Banding on work clothes, jeans and inserting elastic on bathing trunks, sports clothes, boxer shorts and similar tubular articles etc.

Variety	DCN-27
Max. speed	4,000s.p.m.
Max. stitch length	6.4mm
Presser foot lift	8.0mm
Needle bar stroke	31.8mm
Needle	DV×57 #22, 62×57 #140
Thread	#30 (standard)
Lubrication	Hand type
Cylinder size	100mm×130mm×124mm



AC SERVO MOTOR

HVP-i70

FOR "SEIKO" COMMON MODEL

- *Simple and easy to use for "SEIKO" sewing machines. Machine code number for major SEIKO models is available.
- *Specification matched the "CE" standard.
- *Solenoid over current protected.
- *Fully digital design, powerful parameter built-in for application.
- *With over current, overvoltage and brownout protect function by built-in software.
- *With auto-running timer inside for easy to test.
- *Easy to maintain through error code display.

Variety	HVP-i70
Rated speed	3,500r.p.m.
Rated output	750W
Power voltage range	100V - 120V / 200V - 240V
Pulley size available	65mm - 85mm
Gross weight	10.9Kg
Packing dimension (L×W×H)	400mm × 350mm × 320mm




HVP-i90

FOR EXTRA HEAVY DUTY MACHINE

- *Highly accurate positioning even extra heavy duty sewing machine such as CH, TH, JW-A type and SLH series.
- *Low noise, low vibration and low power consumption.
- *Specification matched the "CE" standard.
- *Solenoid over current protected.
- *Fully digital design, powerful parameter built-in for application.
- *Software / Hardware 2-way protection system.
- *Easy to maintain through error code display.

Variety	HVP-i90
Rated speed	2,000r.p.m.
Rated output	750W
Power voltage range	100V - 120V / 200V - 240V
Pulley size available	65mm - 85mm
Gross weight	11.5Kg
Packing dimension (L×W×H)	420mm × 400mm × 350mm







SEIKO SEWING MACHINE CO., LTD.

2-13-6 Sakaecho, Funabashi-shi, Chiba 273-0018, JAPAN

Phone: +81-47-420-3561 (Export dept.)

Fax: +81-47-420-3560

E-mail: export@seiko-sewing.co.jp http://www.seiko-sewing.co.jp